

LCD-4700HD

with
RS-232 and
HDMI & DVI

The Biggest Thing in LCD HD Monitors



Active Matrix 47" Color LCD HD Monitor

• True HD displays 1080p/i without down scaling.
(also supports 480p/i, 576p/i, 720p)

• RS-232 feature allows external devices to
control the monitor through the serial port.

• PIP: Picture in picture capability

- 2 built-in speakers provide 3D MTS stereo and superior listening pleasure.
- SRS technology provides surround sound experience.
- Environmental protection includes power-saving capabilities, and the unit emits no x-radiation.
- Absence of video oscillations and user selection of color temperature (9300°, 7500°, 6500°) provides enhanced viewing pleasure.
- Hard anti-glare coating enhances viewing pleasure.
- Composite, S-Video, component, HDMI, DVI, and PC capability
- Top controls for channel up/down, volume up/down, source, menu
- Case made of durable plastic (black color)
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- Built-in removable desk stand included
- Includes built-in power supply 100~200 VAC.
- Wireless remote control works within 30 feet.
- Widescreen 16:9 aspect ratio, 4:3, zoom

Optional Accessories

- WM-4700VT Heavy duty dual arm mount for LCD-4700HD, 200 lbs. limit, 4-way adjustable
- WM-3742 Fixed wall mount bracket



WM-3742

Resolution: 1920 (H) x 1080 (V) dots

Brightness rating: 550 cd/m² (Nit)

Contrast Ratio: 1600:1

Display: 47.0" TFT LCD active matrix

Back Light: Built-in (24 CCFT)

Input Signal: Composite NTSC/PAL, S-Video, component, analog RGB, HDMI, DVI

PC compatibility: IBM compatible

Dot Pitch: 0.5415(V) x 0.5415(H)mm

Colors: 16.7M

Number of Pixels: 2,073,600

Response Time: 8/8mS (rising/falling)

Audio output: 10W x 2

Speakers (separate): 10W + 10W

Viewing angle L/R/T/B: 89/89/89/89 degrees

Pixel Configuration: Stripe

Input Signal Level: 1.0V P-P (positive) 75 Ohm

Dimensions (WHD): 1165 x 870 x 340mm / 45.9" x 34.3" x 13.4"

Dimension w/o deskstand 1165 x 830 x 130mm / 45.9" x 32.7" x 5.1"

Actual visible screen size (WH): 1018 x 572mm / 42.6" x 22.5"

Operating temperature/humidity: 50 ~ 104°F / 10 ~ 40°C, 20% ~ 90% humidity

Power Requirements: 100 ~ 240 VAC, 50/60 Hz

Power Consumption: 236 W (max)

Rear Terminal Connections: [RCA video IN and RCA R/L IN audio jack] x 2

S-Video IN jack x 2, [RCA Y/Pb/Pr inputs & R/L audio inputs],

[RCA Y/Cb/Cr & R/L audio inputs]

RCA audio R & L output, PC audio IN jack,

15-pin D-sub, AC IN, 9-pin RS-232,

HDMI, DVI

Net Weight: 80.9 lbs. w/o desk stand

Gross Weight: 100.4 lbs.

1319 Dexter Ave. N • Ste. 020 • WA 98109

Tel: 206-623-6000 • FAX: 206-623-6609

E-mail: sales@totevision.com

http://www.totevision.com

**TOTE
VISION**